





KAD LED
LED Area Luminaire



151 511 513



DALI
Dimming
Interface

| | |
|----------------------|-----|
| Control Interface | 700 |
| Power | |

The Conour® Sales luminaires offer traditional lighting technology and meet the highest level of technical standards.

Introduced Series

The Contour® Series luminaires offer traditional square apertures with softened edges for a versatile look that complements many applications.

The KAD LED combines the latest in LED technology, with the familiar aesthetic of the Contour® Series for stylish, high-performance illumination that lasts. It is ideal for replacing 100-250W metal halide in area lighting applications with typical energy savings of 65% and expected service life of over 100,000 hours.

[illegible]

Figure 1 consists of two parts. The top part is a schematic diagram of a drilling process. It shows a drill bit with a diameter of 10 mm and a length of 10 mm. The bit is positioned above a workpiece, with a gap of 0.1 mm between them. The workpiece is labeled 'Top of Hole' and 'Bottom of Hole'. The bottom part is a graph showing the drilling process. The x-axis is labeled 'Time (min)' and ranges from 0 to 10. The y-axis is labeled 'Depth (mm)' and ranges from 0 to 10. The graph shows a curve representing the drilling process, with a peak at approximately 5 minutes and 5 mm depth. The curve is labeled 'Drilling Process' and 'Hole Depth (mm)'. Below the graph is a table of experimental results.

| Time (min) | Depth (mm) | Force (N) | Temperature (°C) |
|------------|------------|-----------|------------------|
| 0 | 0 | 0 | 20 |
| 1 | 1 | 10 | 25 |
| 2 | 2 | 20 | 30 |
| 3 | 3 | 30 | 35 |
| 4 | 4 | 40 | 40 |
| 5 | 5 | 50 | 45 |
| 6 | 4 | 40 | 40 |
| 7 | 3 | 30 | 35 |
| 8 | 2 | 20 | 30 |
| 9 | 1 | 10 | 25 |
| 10 | 0 | 0 | 20 |

[illegible][illegible]